






DICOUSTIC

Acoustic PET Felt Panels

F-PC017- Analogue

1200 x 2400 x 12 mm 1200 x 2400 x 24 mm
1200 x 2780 x 12 mm 1200 x 2780 x 24 mm
1200 x 3000 x 12 mm* 1200 x 3000 x 24 mm*



Product Specifications

Panel Dimensions*	1200 mm x 2400 mm 1200 mm x 2780 mm 1200 mm x 3000 mm* * Custom sizes MOQ = 750 Sqm
Composition	Min. %75 post-consumer recycled materials (PET Bottles)
Tolerance	± %0.5
Thickness	12 mm , 24 mm
Thermal Performance	DI-Panel 12 mm (R0.41 (@15c) DI-Panel 24 mm (R0.82 (@15c)
Microbial Resistance	ASTM (G15- 21) Growth rating: 0 (No Growth) Dicooustic Panel does not promote the growth of moulds and mildew
Absorption Coefficient According to ISO 354	(12 mm) - NRC 0.45 (12 mm with 25 mm air gap) - NRC 0.7 (24 mm) - NRC 0.7 (24 mm with 25 mm air gap) - NRC 0.8
VOC	Private Office-Wall-Pass School Classroom-Wall-Pass Single Family Residence-Wall-Pass Private Office-Ceiling-Pass School Classroom-Ceiling-Pass Single Family Residence-Ceiling-pass
Fire ratings	EN13501-1:2018 Class B-s2,d0 **ASTM E84-2018 Class A ** Optional

Acoustical

Easy Install

Fire Rated

Easy Clean

Printable

Light Weight

Recyclable

Recycled PET

VOC Free

Insulation

Impact Resistant

Antimicrobial

Tackable

5 YEAR WARRANTY

Custom colors MOQ 1500 Sqm
For further cleaning details please refer to our DICOUSTIC Product Cleaning Guide

Acoustic PET Felt Color Range

