




DICOUSTIC

Acoustic PET Felt Panels

F-PC006-Braid

1200 x 2669 x 12 mm
1200 x 2669 x 24 mm



Product Specifications

Panel Dimensions*	1200 mm x 2669 mm * Custom sizes MOQ = 750 Sqm
Composition	Min. %75 post-consumer recycled materials (PET Bottles)
Tolerance	± %0.5
Thickness	12 mm , 24 mm
Thermal Performance	DI-Panel 12 mm (R0.41 (@15c) DI-Panel 24 mm (R0.82 (@15c)
Microbial Resistance	ASTM (G15- 21) Growth rating: 0 (No Growth) Dicooustic Panel does not promote the growth of moulds and mildew
Absorption Coefficient According to ISO 354	(12 mm) - NRC 0.45 (12 mm with 25 mm air gap) - NRC 0.7 (24 mm) - NRC 0.7 (24 mm with 25 mm air gap) - NRC 0.8
VOC	Private Office-Wall-Pass School Classroom-Wall-Pass Single Family Residence-Wall-Pass Private Office-Ceiling-Pass School Classroom-Ceiling-Pass Single Family Residence-Ceiling-pass
Fire ratings	EN13501-1:2018 Class B-s2,d0 **ASTM E84-2018 Class A ** Optional
Acoustical Easy Install Fire Rated Easy Clean Printable Light Weight Recyclable Recycled PET VOC Free Insulation Impact Resistant Antimicrobial Tackable 5 Year Warranty Custom colors MOQ 1500 Sqm For further cleaning details please refer to our DICOUSTIC Product Cleaning Guide	

Acoustic PET Felt Color Range

