






DICOUSTIC

Acoustic PET Felt Panels

F-PC003 - Maze

1200 x 2400 x 12 mm 1200 x 2400 x 24 mm
1200 x 3200 x 12 mm* 1200 x 3200 x 24 mm*



Product Specifications

Panel Dimensions*	1200 mm x 2400 mm 1200 mm x 3200 mm* * Custom sizes MOQ = 750 Sqm
Composition	Min. %75 post-consumer recycled materials (PET Bottles)
Tolerance	± %0.5
Thickness	12 mm , 24 mm
Thermal Performance	DI-Panel 12 mm (R0.41 (@15c) DI-Panel 24 mm (R0.82 (@15c)
Microbial Resistance	ASTM (G15- 21) Growth rating: 0 (No Growth) Dicooustic Panel does not promote the growth of moulds and mildew
Absorption Coefficient According to ISO 354	(12 mm) - NRC 0.45 (12 mm with 25 mm air gap) - NRC 0.7 (24 mm) - NRC 0.7 (24 mm with 25 mm air gap) - NRC 0.8
VOC	Private Office-Wall-Pass School Classroom-Wall-Pass Single Family Residence-Wall-Pass Private Office-Ceiling-Pass School Classroom-Ceiling-Pass Single Family Residence-Ceiling-pass
Fire ratings DICOUSTIC Panels has been evaluated using the following test method	EN13501-1:2018 Class B-s2,d0 **ASTM E84-2018 Class A ** Optional
Acoustical Easy Install Fire Rated Easy Clean Printable Light Weight Recyclable Recycled PET VOC Free Insulation Impact Resistant Antimicrobial Tackable Warranty Custom colors MOQ 1500 Sqm. For further cleaning details please refer to our DICOUSTIC Product Cleaning Guide	

Acoustic PET Felt Color Range

